

## TECHNICAL DATA SHEET

# NR/SBR

# 0104

### DESCRIPTION

- 50°Sh black NR/SBR. Abrasion of 100 (5N). Smooth, matte and fabric impression. Possibility of adding textile and metallic inserts.

### COLOUR:

- Black






### FEATURES

### APPLICATIONS

### TECHNICAL PROPERTIES

	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,13 +/- 0,03	g/cm <sup>3</sup>	UNE 53526
HARDNESS	50 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	5 min	MPa	UNE-ISO 37
ELONGATION	220 min	%	UNE-ISO 37
ABRASION (5N)	100 max	mm <sup>3</sup>	UNE-ISO 4649
TEAR STRENGTH ANGLE	16 min	kg/cm	UNE-ISO 34-1
WORKING TEMPERATURE	-25/+80	°C	

### CHEMICAL RESISTANCE

OZONE RESISTANCE	MODERATE	
WEATHER RESISTANCE	MODERATE	
OIL RESISTANCE	LOW	
ACID RESISTANCE	MODERATE	
BASE RESISTANCE	MODERATE	

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

[www.idcrubber.com](http://www.idcrubber.com)