

TECHNICAL DATA SHEET

SBR

0110

DESCRIPTION

- 70°Sh black SBR. Abrasion of 100 (5N). Smooth, matte and fabric impression. Possibility of adding textile and metallic inserts.

COLOUR:

- Black






FEATURES

APPLICATIONS

TECHNICAL PROPERTIES

| | VALUE | UNIT | STANDARD |
|---------------------|---------------|-------------------|----------------|
| SPECIFIC WEIGHT | 1,49 +/- 0,03 | g/cm ³ | UNE 53526 |
| HARDNESS | 70 +/- 5 | °Sh A | DIN ISO 7619-1 |
| TENSILE STRENGTH | 4 min | MPa | UNE-ISO 37 |
| ELONGATION | 150 min | % | UNE-ISO 37 |
| TEAR STRENGTH ANGLE | 12 min | kg/cm | UNE-ISO 34-1 |
| WORKING TEMPERATURE | -10/+70 | °C | |

CHEMICAL RESISTANCE

| | | |
|--------------------|------------|---|
| OZONE RESISTANCE | MODERATE |  |
| WEATHER RESISTANCE | MODERATE |  |
| OIL RESISTANCE | LOW |  |
| ACID RESISTANCE | ACCEPTABLE |  |
| BASE RESISTANCE | ACCEPTABLE |  |

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com