

TECHNICAL DATA SHEET

SBR

0210

DESCRIPTION

- 65°Sh red SBR. Smooth, matte and fabric impression. Excellent for valves.






COLOUR:

- Red

FEATURES

APPLICATIONS

TECHNICAL PROPERTIES			
	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,62 +/- 0,03	g/cm ³	UNE 53526
HARDNESS	65 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	4 min	MPa	UNE-ISO 37
ELONGATION	400 min	%	UNE-ISO 37
TEAR STRENGTH	15 min	kg/cm	UNE-ISO 34-1
WORKING TEMPERATURE	-10/+70	°C	

CHEMICAL RESISTANCE		
OZONE RESISTANCE	MODERATE	
WEATHER RESISTANCE	MODERATE	
OIL RESISTANCE	LOW	
ACID RESISTANCE	ACCEPTABLE	
BASE RESISTANCE	ACCEPTABLE	

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com