

## TECHNICAL DATA SHEET

# SBR

# 0211

### DESCRIPTION

- 65°Sh white SBR. Smooth, matte and fabric impression. Excellent for valves.

### COLOUR:

- White

### FEATURES

### APPLICATIONS

#### TECHNICAL PROPERTIES

|                     | VALUE         | UNIT              | STANDARD       |
|---------------------|---------------|-------------------|----------------|
| SPECIFIC WEIGHT     | 1,62 +/- 0,03 | g/cm <sup>3</sup> | UNE 53526      |
| HARDNESS            | 65 +/- 5      | °Sh A             | DIN ISO 7619-1 |
| TENSILE STRENGTH    | 4 min         | MPa               | UNE-ISO 37     |
| ELONGATION          | 400 min       | %                 | UNE-ISO 37     |
| TEAR STRENGTH       | 15 min        | kg/cm             | UNE-ISO 34-1   |
| WORKING TEMPERATURE | -10/+70       | °C                |                |

#### CHEMICAL RESISTANCE

|                    |            |   |
|--------------------|------------|---|
| OZONE RESISTANCE   | MODERATE   | ● |
| WEATHER RESISTANCE | MODERATE   | ● |
| OIL RESISTANCE     | LOW        | ● |
| ACID RESISTANCE    | ACCEPTABLE | ● |
| BASE RESISTANCE    | ACCEPTABLE | ● |

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

[www.idcrubber.com](http://www.idcrubber.com)