

TECHNICAL DATA SHEET

SBR

0353

DESCRIPTION

- SBR certified for 30,000 volts in 3mm and 50,000 volts in 4.5mm. Smooth, matte, fabric impression and ribbed finish.

COLOUR:

- Grey

FEATURES

- Isolating rubber sheet certified according to IEC 60243-1:2013 standard.

APPLICATIONS

- Certified for 30.000 volts in 3mm and 50.000 volts in 4,5mm.

TECHNICAL PROPERTIES

	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,61 +/- 0,03	g/cm3	UNE 53526
HARDNESS	65 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	4 min	MPa	UNE-ISO 37
ELONGATION	400 min	%	UNE-ISO 37
TEAR STRENGTH	15 min	Kg/cm	UNE-ISO 34-1
WORKING TEMPERATURE	-10/+70	°C	

CHEMICAL RESISTANCE

OZONE RESISTANCE	MODERATE	●
WEATHER RESISTANCE	MODERATE	●
OIL RESISTANCE	LOW	●
ACID RESISTANCE	ACCEPTABLE	●
BASE RESISTANCE	ACCEPTABLE	●

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com