

TECHNICAL DATA SHEET

SBR

0365

DESCRIPTION

- SBR certified IEC61111:2009 class 0. Smooth, matte, fabric impression and ribbed finish.






COLOUR:

- Grey

FEATURES

APPLICATIONS

TECHNICAL PROPERTIES			
	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,62 +/- 0,03	g/cm ³	UNE 53526
HARDNESS	65 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	3 min	MPa	UNE-ISO 37
ELONGATION	300 min	%	UNE-ISO 37
TEAR STRENGTH ANGLE	15 min	Kg/cm	UNE-ISO 34-1
WORKING TEMPERATURE	-10/+70	°C	

CHEMICAL RESISTANCE	
OZONE RESISTANCE	MODERATE 
WEATHER RESISTANCE	MODERATE 
OIL RESISTANCE	LOW 
ACID RESISTANCE	ACCEPTABLE 
BASE RESISTANCE	ACCEPTABLE 

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com