

## TECHNICAL DATA SHEET

# NR/SBR

# 0809

### DESCRIPTION

- 45°Sh yellow NR/SBR. Excellent elongation and abrasion of 90 (10N). Smooth, matte, fabric impression and bonding layer






### COLOUR:

- Yellow

### FEATURES

### APPLICATIONS

TECHNICAL PROPERTIES			
	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,16 +/- 0,03	g/cm <sup>3</sup>	UNE 53526
HARDNESS	45 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	12 min	MPa	UNE-ISO 37
ELONGATION	600 min	%	UNE-ISO 37
ABRASION (5N)	90 max	mm <sup>3</sup>	UNE-ISO 4649
TEAR STRENGTH ANGLE	18 min	kg/cm	UNE-ISO 34-1
WORKING TEMPERATURE	-25/+80	°C	

CHEMICAL RESISTANCE		
OZONE RESISTANCE	MODERATE	
WEATHER RESISTANCE	MODERATE	
OIL RESISTANCE	LOW	
ACID RESISTANCE	MODERATE	
BASE RESISTANCE	MODERATE	

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

[www.idcrubber.com](http://www.idcrubber.com)