

TECHNICAL DATA SHEET

NR/SBR

1301

DESCRIPTION

- 60°Sh black NR/SBR. Abrasion 90 (10N). Smooth, matte, fabric impression and bonding layer. Possibility of adding inserts.

COLOUR:

- Black

FEATURES

APPLICATIONS

TECHNICAL PROPERTIES

	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,15 +/- 0,03	g/cm ³	UNE 53526
HARDNESS	60 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	16 min	MPa	UNE-ISO 37
ELONGATION	400 min	%	UNE-ISO 37
ABRASION (10N)	90 max	mm ³	UNE-ISO 4649
TEAR STRENGTH ANGLE (UNE-ISO 34-1)	45 min	kg/cm	UNE-ISO 34-1
WORKING TEMPERATURE	-25/+80	°C	

CHEMICAL RESISTANCE

OZONE RESISTANCE	MODERATE	●
WEATHER RESISTANCE	MODERATE	●
OIL RESISTANCE	LOW	●
ACID RESISTANCE	MODERATE	●
BASE RESISTANCE	MODERATE	●

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com