

## TECHNICAL DATA SHEET

# NR

# 1313

### DESCRIPTION

- 60°Sh black NR/SBR. Abrasion 165 (10N). Smooth, matte, fabric impression and bonding layer. Possibility of adding inserts.

### COLOUR:

- Black

### FEATURES

### APPLICATIONS

#### TECHNICAL PROPERTIES

	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,09 +/- 0,03	g/cm <sup>3</sup>	UNE 53526
HARDNESS	60 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	18 min	MPa	UNE-ISO 37
ELONGATION	400 min	%	UNE-ISO 37
ABRASION (10N)	165 max	mm <sup>3</sup>	UNE-ISO 4649
TEAR STRENGTH ANGLE	35 min	kg/cm	UNE-ISO 34-1
WORKING TEMPERATURE	-40/+80	°C	

#### CHEMICAL RESISTANCE

OZONE RESISTANCE	MODERATE	●
WEATHER RESISTANCE	MODERATE	●
OIL RESISTANCE	LOW	●
ACID RESISTANCE	ACCEPTABLE	●
BASE RESISTANCE	ACCEPTABLE	●

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

[www.idcrubber.com](http://www.idcrubber.com)