

TECHNICAL DATA SHEET

NR/SBR

1319

DESCRIPTION

- 62°Sh black NR/SBR. Good abrasion of 130 (10N). Smooth, matte, fabric impression and bonding layer. Possibility of adding inserts.

COLOUR:

- Black






FEATURES

APPLICATIONS

TECHNICAL PROPERTIES

	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,15 +/- 0,03	g/cm ³	UNE 53526
HARDNESS	62 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	9 min	MPa	UNE-ISO 37
ELONGATION	350 min	%	UNE-ISO 37
ABRASION (10N)	130 max	mm ³	UNE-ISO 4649
TEAR STRENGTH ANGLE (UNE-ISO 34-1)	40 min	kg/cm	UNE-ISO 34-1
WORKING TEMPERATURE	-25/+80	°C	

CHEMICAL RESISTANCE

OZONE RESISTANCE	MODERATE	
WEATHER RESISTANCE	MODERATE	
OIL RESISTANCE	LOW	
ACID RESISTANCE	MODERATE	
BASE RESISTANCE	MODERATE	

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com