

## TECHNICAL DATA SHEET

# NR/SBR

# 1368

### DESCRIPTION

- 45°Sh yellow NR/SBR. Very good elongation and abrasion of 80 (5N). Smooth, matte, fabric impression and bonding layer.

### COLOUR:

- Yellow






### FEATURES

### APPLICATIONS

#### TECHNICAL PROPERTIES

|                     | VALUE          | UNIT              | STANDARD       |
|---------------------|----------------|-------------------|----------------|
| SPECIFIC WEIGHT     | 1,05 +/- 0,03  | g/cm <sup>3</sup> | UNE 53526      |
| HARDNESS            | 45 +/- 5       | °Sh A             | DIN ISO 7619-1 |
| TENSILE STRENGTH    | 15 min         | MPa               | UNE-ISO 37     |
| ELONGATION          | 600 min        | %                 | UNE-ISO 37     |
| ABRASION (5N)       | 80 max         | mm <sup>3</sup>   | UNE-ISO 4649   |
| TEAR STRENGTH ANGLE | 22 Mean values | kg/cm             | UNE- ISO 34-1  |
| WORKING TEMPERATURE | -25/+80        | °C                |                |

#### CHEMICAL RESISTANCE

|                    |          |   |
|--------------------|----------|---|
| OZONE RESISTANCE   | MODERATE |  |
| WEATHER RESISTANCE | MODERATE |  |
| OIL RESISTANCE     | LOW      |  |
| ACID RESISTANCE    | MODERATE |  |
| BASE RESISTANCE    | MODERATE |  |

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

[www.idcrubber.com](http://www.idcrubber.com)