

## TECHNICAL DATA SHEET

# SPECIAL NR

# 1372

### DESCRIPTION

- 55°Sh black NR. Excellent abrasion of 70 (5N). Smooth, matte and fabric impression. Possibility of adding inserts.

### COLOUR:

- Black






### FEATURES

### APPLICATIONS

### TECHNICAL PROPERTIES

	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,14 +/- 0,03	g/cm <sup>3</sup>	UNE 53526
HARDNESS	55 +/- 5	° Sh A	DIN ISO 7619-1
TENSILE STRENGTH	17 min	MPa	UNE-ISO 37
ELONGATION	400 min	%	UNE-ISO 37
ABRASION (5N)	70 max	mm <sup>3</sup>	UNE-ISO 4649
TEAR STRENGTH ANGLE	50 min	kg/cm	UNE-ISO 34-1
REBOUND RESILIENCE %	70 Mean values	%	UNE-ISO 4662
MODULUS 500%	6 Mean values	%	UNE-ISO 37
WORKING TEMPERATURE	-50/+80	°C	

### CHEMICAL RESISTANCE

OZONE RESISTANCE	MODERATE	
WEATHER RESISTANCE	MODERATE	
OIL RESISTANCE	LOW	
ACID RESISTANCE	ACCEPTABLE	
BASE RESISTANCE	ACCEPTABLE	

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

[www.idcrubber.com](http://www.idcrubber.com)