

TECHNICAL DATA SHEET

CSM

1401

DESCRIPTION

- 65°Sh Hypalon®. Excellent properties and price. Smooth finish and fabric impression.

COLOUR:

- Black






FEATURES

- Hypalon® rubber sheet with good properties and excellent quality-price ratio.

APPLICATIONS

- Gaskets, flanges, applications with weather conditions and/or offshore.

TECHNICAL PROPERTIES			
	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,39 +/- 0,03	g/cm3	UNE 53526
HARDNESS	65 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	10 min	MPa	UNE-ISO 37
ELONGATION	200 min	%	UNE-ISO 37
COMPRESSION SET (24h/ 70 °C)	35 Mean values	%	UNE-ISO 845-1
WORKING TEMPERATURE	-30/+125	°C	

CHEMICAL RESISTANCE		
OZONE RESISTANCE	EXCELLENT	
WEATHER RESISTANCE	EXCELLENT	
OIL RESISTANCE	GOOD	
ACID RESISTANCE	GOOD	
BASE RESISTANCE	GOOD	

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com