

TECHNICAL DATA SHEET

EPDM

2130

DESCRIPTION

- EPDM certified EN45545, R22, R23, HL1, HL2 and HL3. Smooth, matte and fabric impression

COLOUR:

- Black

FEATURES






- EPDM fire resistance according to EN 45545-2. Meets the requirements R22, R23, hazard level HL1, HL2, HL3.

APPLICATIONS

TECHNICAL PROPERTIES

	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,44 +/- 0,03	g/cm ³	UNE 53526
HARDNESS	70+/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	5 min	MPa	UNE-ISO 37
ELONGATION	350 min	%	UNE-ISO 37
WORKING TEMPERATURE	-35/+120	°C	

CHEMICAL RESISTANCE

OZONE RESISTANCE	EXCELLENT	
WEATHER RESISTANCE	EXCELLENT	
OIL RESISTANCE	NOT SUITABLE	
ACID RESISTANCE	GOOD	
BASE RESISTANCE	EXCELLENT	

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com