

## TECHNICAL DATA SHEET

# EPDM

# 2142

### DESCRIPTION

- 60°Sh red EPDM. Excellent resistance to ozone, weather, and alkalis.






### COLOUR:

- Red

### FEATURES

### APPLICATIONS

TECHNICAL PROPERTIES			
	VALUE	UNIT	STANDARD
SPECIFIC WEIGHT	1,28 +/- 0,03	g/cm <sup>3</sup>	UNE 53526
HARDNESS	60 +/- 5	°Sh A	DIN ISO 7619-1
TENSILE STRENGTH	8 min	MPa	UNE-ISO 37
ELONGATION	350 min	%	UNE-ISO 37
WORKING TEMPERATURE	-35/+120	°C	

CHEMICAL RESISTANCE		
OZONE RESISTANCE	EXCELLENT	
WEATHER RESISTANCE	EXCELLENT	
OIL RESISTANCE	NOT SUITABLE	
ACID RESISTANCE	GOOD	
BASE RESISTANCE	EXCELLENT	

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

[www.idcrubber.com](http://www.idcrubber.com)