

TECHNICAL DATA SHEET

DYC

PEROXYDE EPDM

2162

DESCRIPTION

 50°Sh black peroxide EPDM.
Excellent resistance to ozone, weather, alkalis and high temperatures.

COLOUR:

Black

FEATURES

APPLICATIONS

| TECHNICAL PROPERTIES | | | |
|----------------------|---------------|-------|----------------|
| | VALUE | UNIT | STANDARD |
| SPECIFIC WEIGHT | 1,18 +/- 0,03 | g/cm3 | UNE 53526 |
| HARDNESS | 50 +/- 5 | ∘Sh A | DIN ISO 7619-1 |
| TENSILE STRENGTH | 7 min | MPa | UNE-ISO 37 |
| ELONGATION | 300 min | % | UNE-ISO 37 |
| WORKING TEMPERATURE | -40/+150 | °C | |

| CHEMICAL RESISTANCE | | |
|---------------------|--------------|--|
| OZONE RESISTANCE | EXCELLENT | |
| WEATHER RESISTANCE | EXCELLENT | |
| OIL RESISTANCE | NOT SUITABLE | |
| ACID RESISTANCE | GOOD | |
| BASE RESISTANCE | EXCELLENT | |

The technical information contained in this data sheet is the result of performing tests on laboratory samples according to the standards mentioned above. The customer is responsible for evaluating the suitability of the product according to their specific requirements. Values may be updated without prior notice.

www.idcrubber.com

Ctra. Artica 16 | 31013 Artica | Navarra (Spain) **T** +34 948 145 388 | F +34 948 126 032 idcrubber@grupoelastorsa.com

GRUPO 🖪 ELASTORSA